

DTS-RSxx



DTS-RS

SERIES

DTS-RSxx

The DTS-RSxx Series is a high performance 8U, 17 & 19" LCD Monitor made from Zinc Plated Steel Chassis and a Powder Coated Milled Aluminum Front Face. It offers LED Back Lit LCD Panels with high contrast ratios and wide viewing angles. With only 3" of depth this display will fit into your next rack, panel, in wall or Kiosk project. It can be used in Industrial, Commercial, Broadcast, Home Automation or Military applications. It has options for PCAP and Resistive Touch with serial /USB interface choices. Other options include High Bright Back Light, NVIS, and Optical Bonding.

DIT: THE INDUSTRY LEADER IN RACK MOUNT DISPLAY SOLUTIONS



FEATURES

- A** LED Backlit LCDs
- B** Unified OSD Buttons
- C** Milled Aluminum Front Face
- D** 8 Rack Units
- E** Power Inlet Plate*
*Choice from 5 Std Connector and any Custom Ones you want.
- F** Multiple Controllers to Choose From
- G** Zinc Plated Steel Construction

WHY CHOOSE THE DTS-RSxx?

- Rugged Steel and Aluminum Construction
- Rack Mount Monitor
- Fits Inside 19" Rack Frame
- Utilizes only 8U (14.00") On The Rack
- Low Power Consumption
- Touch Screen Option Available
- Compact enclosure for Rackmount and Panel applications

*Additional mounting options available

CONTROLLERS

- **V14X Embedded Controller (Legacy)**
Max Resolution: 1920 x 1200
Input Options Available: VGA, DV-D, CVS, S-Video, YPbPr
Audio: Optional
- **V23xM Embedded Controller**
Max Resolution: 1920 x 1200
Input Options Available: VGA, DVI, HDMI
YPbPr, 3G-SDI, Conformal Coated Board
- **V33X Embedded Controller**
Max Resolution: 1920 x 1200
Input Options Available: VGA, Display Port, HDMI
Audio: Optional

*Additional Controller Options Available

LCD DETAILS

17L SXGA 1280 x 1024 (Max Res)

- LED Back Light
- Viewing Angles: 85/85/80/80
- Contrast Ratio: 1000:1
- Response Time: 5ms
- Brightness: 350 nits
- Response Time: 5ms

19L SXGA 1280 x 1024 (Max Res)

- Twisted Nematic Panels
- LED Back Light
- Viewing Angles: 85/85/80/80
- Contrast Ratio: 1000:1
- Response Time: 5ms
- Brightness: 350 nits
- Optional: Optical Bond & Touch

*Additional Panel Options Available including High Bright and NVIS

FEATURES AND OPTIONS

- Optional Resistive and PCAP-Touch
- High Bright LCD Panels
- OSD (On Screen Display) Controls
- Optical Bonding



SERIES:
DTS-RS

DISPLAY:
17L
└──┘
19L, 19HB, 17N

CONTROL-
V14x
└──┘
V23xM, V33x

SPECIFICATIONS

- Dimensions: 15.75" (H) x 19"W x 3"D
- Weight: 20 Lbs
- Power Consumption: ~30 Watts

Values are approximate and vary based on configuration

► Custom Options Available On All DIT Models



DIT: Display Integration Technologies | The Worlds Most Configureable Monitors
1357 Rocky Point Drive, Oceanside CA 92056 | 760.599.9225 | www.DITHD.com

