

RD1U-S20

S-CLASS



SERIES

RD1U-S20

The RD1U-S20 is an all Aluminum 1U KVM Rack Drawer With the Keyboard and Monitor Moving Independent of each other so we call it a Split Rack Drawer or S-Class. It is super Light Weight Coming In at Less than 30 Lbs. We now Support Multiple Monitor Sizes, Lens Enhancements, and Touch Options. We have Recently upgraded the Rear KVM Electronics with Multiple New KVM and AD Card Options.

DIT: THE INDUSTRY LEADER IN RACK MOUNT DISPLAY SOLUTIONS



FEATURES

- A** LED Back Lit LCD With Lens Enhancement
- B** Multiple Front Face and Handle Options
- C** Optional Collapsible Handle
- D** Multiple Back and KVM Switch options
- E** 2 Pin Locking Power Inlet
- F** Telescoping Transit Case Arms
- G** Grounding Stud
- H** Dual Slide Rail System
- I** Dual Cable Guide System
- J** 104 Key Keyboard with Cirque Glidepad

WHY CHOOSE THE RD1U-S20?

- Split design- independent LCD and keyboard drawer
- Customizable modular design
- Low Profile Stealth keyboard and pointer
- LED backlit LCDs
- Rugged all aluminum construction
- Small 1U Form Factor

*Additional mounting options available

LCD OPTIONS (MAX RES)

- 15L** LED XGA 1024 x 768
- 15N** NVIS XGA 1024 x 768
- 15HB** High Bright XGA 1024 x 768
- 17L** LED Backlit SXGA 1280 x 1024
- 17HB** High Bright SXGA 1280 x 1024
- 173W** LED Backlit FHD 1920 x 1080
- 173HB** High Bright FHD 1920 x 1080

VIDEO CONTROLLERS

- **V13X Controller**
Max Resolution 1920 x 1200
VGA, Audio HDMI, Display Port
- **V17X Controller**
Max Resolution: 1920 x 1200
VGA, Audio, HDMI, Display Port
- **V252 Controller**
Max Resolution 1920 x 1200
VGA, DVI

Additional Controller Options Available

FRONT FACES

D1: Double thumb screw w/ pocket pull handle



D7: Double thumb screw w/ 5" flush collapsible handle



Enhancement Options:

- Anti-Reflective Lens
- ITO Lens
- Resistive Touch
- Projected Capacitive Touch
- Conformal Coating

KEYBOARDS



Bu: 104 Key Keyboard (USB) w/ Cirque Glide Pad

Power Options

Standard: 12 VDC 2 Pin Locking Connector

Wide Range: 9-36 VDC 2 Pin Locking Connector

KVMs



E3u 8 port VGA/USB KVM switch option



U5K 4 port VGA KVMA switch option

Please contact sales rep to hear other keyboard, KVM, Power, Video Controller and Custom options.

SPECIFICATIONS

- Dimensions: 1.75" (1U) x 19"W x 20"D
- Weight: 23 Lbs
- Power Consumption: ~35 Watts
- Operating Temp: -20 to 85 C

Values are approximate and vary based on configuration

► Custom Options Available On All DIT Models



SERIES
RD1U-S20

DISPLAY
17L
17L, 17HB
173W,
and more

KEYBOARD
Bu
More
to Come

BACK/KVM
E3u
A-X

CONTROLLER
V25X
V18X, V25X,
and more

FRONT FACE
E8
E (Faces)
1-9 (Handles)



DIT: Display Integration Technologies | The Worlds Most Configureable Monitors
1357 Rocky Point Dr. Oceanside CA, 92056 | 760.599.9225 | www.DITHD.com

